



FM 80

 Filtro con cartuccia intercambiabile. Ideale per alimentazione applicatori in linea di smaltatura. Disponibile nella versione con barrotto magnetico.

 Filter with interchangeable cartridge. Ideal for feeding applicators in a glazing line. Version with magnetic bar available.

 Filtro con cartucho intercambiabile. Ideal para alimentación de aplicadores en línea de esmaltado. Disponible en la versión con barrote magnético.

 Filtre à cartouche interchangeable. Idéal pour alimenter les applicateurs en ligne d'émaillage. Disponible dans la version avec barreau magnétique.



32 MESH



50 MESH



80 MESH



100 MESH



120 MESH



150 MESH

Caratteristiche tecniche Technical features Características técnicas Caractéristiques techniques	FM 80
Potenza magnetica in campo chiuso (Gauss) Magnetic power in close field (Gauss) Potencia magnética en campo cerrado (Gauss) Puissance magnétique en champ fermé (Gauss)	12.000
Barra magnetica (mm) Magnetic bar (mm) Barra magnética (mm) Barre magnétique (mm)	n°1 ø25x120
Max. pressione esercizio (bar) Max. operating pressure (bar) Max. presión funcionam. (bar) Pression Max. service (bar)	1,5
Temp. Max. di esercizio (°C) Max. operating temperature (°C) Temp. Max. de funcion (°C) Temp. Max. de service (°C)	60
Peso (Kg) Weight (Kg) Peso (Kg) Poids (Kg)	1,6